


TEE Reto

Extremidades prolongadas para solda orbital

DT-4.1.2-1 (DT-9)



IMDI BioClean



Ø (Diâmetro)	OD	ID	Esp.	A	B
1/4"	6,35	4,57	0,89	44,5	44,5
3/8"	9,53	7,75	0,89	44,5	44,5
1/2"	12,7	9,4	1,65	47,6	47,6
3/4"	19,05	15,75	1,65	50,8	50,8
1"	25,4	22,1	1,65	54,0	54,0
1.1/2"	38,1	34,8	1,65	60,3	60,3
2"	50,8	47,5	1,65	73,0	73,0
2.1/2"	63,5	60,2	1,65	79,4	79,4
3"	76,2	72,9	1,65	85,7	85,7
4"	101,6	97,38	2,11	104,8	104,8
6"	152,4	146,86	2,77	142,9	142,9

Matéria Prima

ASTM A270 S2 UNS
S31603 (316L)

Acabamento de superfície

Interno

SF1: Ra < 0,50 µm (20 µin)
Polimento Mecânico

SF4: Ra < 0,375 µm (15 µin)
Eletropolimento

Externo

Ra 0,80 µm (32 µin)

Medidas em mm - Dimensões conforme norma ASME BPE (Tabela DT-3-1)

IMDI IMEDIATO
Inox

www.imediatovalvulas.com.br