


# TEE Reto - Derivação Curta

Extremidades prolongadas para solda orbital x Tri-Clamp

DT-4.1.2-2 (DT-15)



Ø (Diâmetro)	OD	ID	Esp.	A	B
1/4"	6,35	4,57	0,89	44,5	25,4
3/8"	9,53	7,75	0,89	44,5	25,4
1/2"	12,7	9,4	1,65	47,6	25,4
3/4"	19,05	15,75	1,65	50,8	28,6
1"	25,4	22,1	1,65	54,0	28,6
1.1/2"	38,1	34,8	1,65	60,3	34,9
2"	50,8	47,5	1,65	73,0	41,3
2.1/2"	63,5	60,2	1,65	79,4	47,6
3"	76,2	72,9	1,65	85,7	54,0
4"	101,6	97,38	2,11	104,8	69,0
6"	152,4	146,86	2,77	142,9	117,5

## Matéria Prima

ASTM A270 S2 UNS  
S31603 (316L)

## Acabamento de superfície

### Interno

SF1: Ra < 0,50 µm (20 µin)  
Polimento Mecânico

SF4: Ra < 0,375 µm (15 µin)  
Eletropolimento

### Externo

Ra 0,80 µm (32 µin)

Medidas em mm - Dimensões conforme norma ASME BPE (Tabela DT-3-1)